## **Product Leaflet**



## **Aqua Drop**

Water system that secures a constant level of water in the trough

The vacuum controlled water valve secures a constant level of water in the trough. When the water level gets below the water pipe, air flows to the valve and opens the water supply. Once water reaches the pipe again, and thereby the wanted water level, vacuum builds up and stops the water flow. AquaDrop is an ideal alternative to traditional water supply systems where hoses are integrated in pipes and partitions. A small lever at the front makes it easy to close the water supply when pigs are taken out of a pen or a box.

## Aqua Drop piece list:

4900483 - Aqua Drop with 1,2 m water pipe

4900484 - Aqua Drop with 1,5 m water pipe

4900485 - Mounting set for 1" front pipes

4900486 - Mounting set for vertical bars

4900487 - Mounting set for 35-40 mm board profiles

4900488 - Mounting set for 50 mm panels

4900489 - Mounting set for walls

## Recommendations:

The water supply must have a filter.

Recommended water pressure 2,0 - 2,5 bar.

The water pipe should be placed as far away as possible from the feed outlet.

The water pipe must be cleaned on a regularly basis to avoid hygienic problems.

The water pipe must be minimum 80 cm and maximum 200 cm long. The valve should be mounted out of reach of the pigs.

For easy and simple water connection Aqua Drop has 2 entrances with 1/2" female thread for horizontal and vertical water pipe. By delivery a plug to close one of the two entrances is included.

